

MATERIAL/PRODUCT SAFETY DATA SHEET

1. Identification of the Substance or Preparation and Company

1.1 Product : Lithium/Thionyl Chloride(Li/SOCl₂) Cells & Batteries(serial-parallel)
and / Sulfuryl Chloride (Li/SO₂Cl₂) Cells & Batteries(serial-parallel)

1.2 Model : TEKCELL (Brand name)

Type	Model	Type	Model	Type	Model
Bobbin	SB-AA02	Wound	SW-AA11	High Temperature	HGDD10A
	SB-AA02(V)		SW-A01		HGDD15A
	SB-AA02HP		SW-C03		HGDD16A
	SB-AA11		SW-D03		HLFD15A
	SB-A01				HGD016A
	SB-C02				MGDD16A
	SB-D02				MG2116A
	SB-D02(V)				MG2516A
		MG2616A			
		PGDD10A			
		PGD010A			
		PGC010A			

1.3 Company

Name : Vitzrocell, Co. Ltd
Address : 70, Indusparkro, Hapdeokeup, Dangjinsi, Chungnam, S.Korea
Tel : +82-41-332-8642
Fax : +82-41-332-8646
Website : www.vitzrocell.com

2. Hazards Identification

The batteries described in this MSDS are hermetically sealed unit, which are not hazardous when used according to the recommendations of the manufacturer. Under normal condition of use of the batteries, the electrode materials and the liquid electrolyte they contained are non-reactive provided the battery integrity is maintained. Risk of exposure exists only in case of mechanical, electrical or thermal abuse. Thus, the batteries should not short circuit, recharge, puncture, incinerate, crush, immerse in water, force discharge, or expose to above the temperature range of the cell or battery. In these cases, there is risk of fire or explosion.

3. Composition & Information on Ingredients

Ingredient	Content (%)	CAS No.	etc
Lithium(Li)	4 ~ 5.5%	7439-93-2	
Carbon (C)	4 ~ 5.5%	1333-86-4	
Electrolyte(SOCl ₂ / SO ₂ Cl ₂)	40 ~ 55%	7719-09-7	
Aluminium Chloride(AlCl ₃)	2 ~ 4.0%	7446-70-0	
STAINLESS STEEL	25 ~ 30%	65997-19-5	
Gallium Chloride(GaCl ₃)	2.0~4.0%	13450-90-3	Only used for SW-D03 and High temp Series instead of AlCl ₃

4. First Aid Measures

Handle according to emergency measures under in case of battery rupture, explosion or leakage and evacuate personnel from contaminated area and provide good ventilation to clear out corrosive fumes, gases or the pungent odour. Seek immediate medical attention.

Inhalation – Remove from exposure, rest and keep warm. In severe cases, obtain medical attention

Skin Contact – Wash off skin thoroughly with flow water for 10~15 minutes and obtain medical attention.

Eye Contact – Irrigate thoroughly with Water for at least 15 minutes and obtain medical attention.

Ingestion – Wash out mouth thoroughly with water and give plenty of water to drink for vomit and obtain medical attention.

5. Fire Fighting Measures

It is effective to use cold water in order to prevent spread of fire caused by lithium cells. However, never use hot water.

Lith-X(Class D extinguishing media) is the only effective on fires involving a few lithium batteries. If the cells are directly involved in a fire, DO NOT USE WATER, SAND, CO₂, HALON and DRY POWDER or SODA ASH EXTINGUISHERS.

If a fire is in adjacent area, and cells are packed in their original containers, the fire can be fought based on fuelling material, e.g. paper and plastic products.

6. Accidental Release Measures

Do not breathe vapours or touch liquid with bare hand. If the skin has come into contact with the electrolyte, take an action in accordance with 4. First Aid Measures.

Graphite powder should be used to absorb the exudation, seal leaking battery and graphite powder in plastic bag and dispose of Special Waste.

7. Handling and Storage

Handling – Prevent short circuit and do not use the battery above the temperature rating of battery. Do not recharge, force over-discharge (voltage below 0.0V), puncture and compress.

Storage – Storage preferably in cool (below 30°C) and non-elevated temperatures place. Storage in high temperatures can result in shortened battery life and degrade performance. Do not store batteries in high humidity, shock and vibration environments.

Others – Do not charge primary battery which is not chargeable battery. Follow manufacturer's recommendations regarding maximum recommended current and operating temperature range.

8. Exposure Controls & Personal Protection

The following safety measures are not necessary in normal use. They need only be applied if there is a risk that, in use or handling, the recommendations, as outlined in Section 3, have not been followed.

Respiratory protection – In all fire situations, use filter mask or self-contained breathing Apparatus for harmful gases or other material prevention.

Hand protection – In leakage situations, use specific gloves for leaking chemical substance and heat prevention.

Eye protection – Use safety goggles or face shield which can separate eyes and the outside for chemical substance and heat prevention.

Other protective equipment – Additional equipments are needed to prevent from chemical substance, harmful material and heat. (Clothes, boots etc.)

9. Physical and Chemical Properties

Appearance	Cylindrical shape
Odour	Odourless. If leaking, gives off a pungent and corrosive odour.
pH	Not applicable (Unless individual components exposed)
Boiling point	Not applicable (Unless individual components exposed)
Vapour pressure (mmHg,25°C)	Not applicable (Unless individual components exposed)
Relative density	Not applicable (Unless individual components exposed)
Flash point	Not applicable (Unless individual components exposed)
Flammability	Not applicable (Unless individual components exposed)
Solubility (water)	Not applicable (Unless individual components exposed)
Solubility (other)	Not applicable (Unless individual components exposed)
Physical state	Solid

10. Stability and Reactivity

Product is stable under conditions described in Section 7 (Handling and storage).

Conditions to avoid – heating and incineration above 90°C, transformation, abscission, compression, puncture, disassembly, charge, a short circuit, storage in high humidity for a long time.

Material to avoid – Prevent to contact Oxidizer, Strong carbonated water, Alkali solutions, Water (H₂O), Aluminium, Zinc, and Electrolyte.

Harmful materials caused by disassembly

1. Water (H₂O) reacts with lithium metal to form powder such as lithium hydroxide (LiOH), lithium oxide and hydrogen gas (H₂)
2. In case of heating the electrolyte above 150°C, chlorine(Cl₂), sulfur dioxide(SO₂), sulphur trioxide(SO₃), disulfur dichloride(S₂Cl₂), sulphur dichloride (SCL₂), lithium oxide(Li₂O) may occur.
3. Water (H₂O) reacts with the electrolyte in room temperature to form hydrochloric acid(HCl) and sulphur dioxide(SO₂).

11. TOXICOLOGICAL INFORMATION

Symptoms and Signs – None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes.

Inhalation – Lung irritant.

Skin contact – Skin irritant

Eye contact – Eye irritant

Ingestion – if swallow, it can be poisoned.

Medical condition aggravated by exposure – In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.

12. Ecological Information

When properly used or disposed the battery does not present environmental hazard.

Cells of Vitzrocell do not contain mercury, cadmium, lead and Cr⁶⁺ which has a bad influence on environment.

13. Disposal Considerations

Do not incinerate or subject cells to temperatures in excess of 85°C. In the event of such abuse can result in loss of seal that causes explosion.

Cells should be separated after use in order to prevent short circuit terminal by using tape or other tools and dispose of in accordance with regulations.

14. Transportation

Compliance with IATA Dangerous Goods Regulation (65th)

Model	Lithium contents(g)	IATA PI968	IMDG
SB-AA02	0.31	Section IB or IA	Non DG
SB-AA02(V)	0.31	Section IB or IA	Non DG
SB-AA02HP	0.31	Section IB or IA	Non DG
SB-AA11	0.71	Section IB or IA	Non DG
SB-A01	0.99	Section IB or IA	Non DG
SB-C02	2.27	section IA	DG
SB-D02	5.00	section IA	DG
SB-D02(V)	5.00	section IA	DG
SW-AA11	0.66	Section IB or IA	Non DG
SW-A01	1.00	section IA	DG
SW-C03	2.40	section IA	DG
SW-D03	4.90	section IA	DG
HGDD10A	8.72	section IA	DG
HGDD15A	8.05	section IA	DG
HGDD16A	7.04	section IA	DG
HLFD15A	11.94	section IA	DG
MGDD16A	8.68	section IA	DG
MG2116A	2.81	section IA	DG
MG2516A	4.05	section IA	DG
MG2616A	4.31	section IA	DG
HGD016A	3.30	section IA	DG
PGDD10A	9.59	section IA	DG
PGD010A	4.06	section IA	DG
PGC010A	2.04	section IA	DG

Lithium cell must pass relevant examination regardless of lithium content. Relevant regulation and examination regulation for product are as follows.

The UN Recommendations on the Transport of Dangerous Goods, Model Regulations

The UN recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part III, Section 38.3

Hazard Classification: Class9

UN Number: 3090 Lithium batteries, 3091 Lithium batteries contained in equipment or Lithium batteries packed with equipment.

Other regulation and guideline

ADR, RID 188, 230, 310, P903

IATA A88, A99, A154, A164

IMDG code SP188, 230, 310, P903

15. Regulatory Information

None

16. Other Information

TEKCELL (manufacturer: Vitzrocell) was recognized safety by UL (Underwriters Laboratories) located in Northbrook, U.S.A. (UL File No. : MH 18384)

(Some cells and batteries are not UL certified)

Vitzrocell has all authorities about this MSDS. In case of use of relevant data by outside presentation, should get permission by Vitzrocell.